正基科技股份有限公司

SPECIFICATION

PRODUCT NAME：AP6611S

REVISION：1.5

DATE：Nov. 21th , 2023

Customer APPROVED	
Company	
Representative Signature	

PREPARED	REVIEW			APPROVED	DCC ISSUE
	PM	QA	ET		

正基科技股份有限公司

AMPAK Technology Inc.

AP6611S

Draft Data Sheet

Address:
8F, No.15-1, Zhonghua Road, Hsinchu Industrial Park, Hukou, Hsinchu,
Taiwan, 30352
Website: http://www.ampak.com.tw/

Revision

Revision	Date	Description	Revised By
0.1	2023/02/14	-- Preliminary release	Ares
0.2	2023/04/15	-- Updated RF performance	Ares
0.3	2023/05/25	-- Updated RF Block diagram	Ares
0.4	2023/06/2	-- Updated Dimension	Ares
0.5	2023/07/27	-- Updated RF specifications	Ares
1.0	2023/10/06	-- Modify Introduction	Ali
1.1	2023/10/06	-- Modify RF specifications	Ali
1.2	2023/10/13	-- Modify RF specifications	Ali
1.3	2023/10/13	-- Modify Pin define	Ali
1.4	2023/10/24	-- Modify Model name	Ali
1.5	2023/11/21	-- Updated Dimension	Ali

Contents

1. Introduction 2
1.1 Overview 2
1.2 Product Features 3
2. General Specification 4
2.1 General Specification 4
2.2 DC Characteristics 4
2.2.1 Absolute Maximum Ratings 4
2.2.2 Recommended Operating Rating 5
3. Wi-Fi RF Specification 6
3.1 2.4GHz RF Specification 6
3.2 5 GHz RF Specification 8
3.3 6GHz RF Specification 14
4. Bluetooth Specification 17
4.1 Bluetooth Specification 17
5. Pin Definition 18
5.1 Pin Outline 18
5.2 Pin Assignment 19
6. Dimensions 21
6.1 Module Dimensions 21
6.2 Recommended footprint 22
7. External clock reference 23
8. Host Interface Timing Diagram 24
8.1 Power-up Sequence Timing Diagram 24
8.2 SDIO Interface Description 26
8.4 UART Interface Description 39
9. Recommended Reflow Profile 41
10. Package Information 42
10.1 Label 42
10.2 Dimension 43
10.3 MSL Level / Storage Condition 45

1. Introduction

1.1 Overview

The AMPAK Technology® AP6611S is a fully Wi-Fi 6E and Bluetooth functionalities module with seamless roaming capabilities and advance security. It is capable of associating with variety of Wi-Fi 6E or legacy Access Points / Routers and run up to PHY rate of 500Mbps with single stream. Furthermore, AP6611S supports SDIO v3.0 / 2.0 interfaces by proper setting for Wi-Fi and UART/ PCM interface for Bluetooth.

In addition, this compact module is a total solution for a combination of Wi-Fi + Bluetooth technologies. The module is specifically developed for tablet, OTT box and portable & mobile devices.



1.2 Product Features

IEEE 802.11 Key Features

- 802.11ax/ac/a/b/g/n compliant
- Radio band support for 2.4 / 5 / 6 GHz band including 6GHz UNII-5,6,7,8
- Support 802.11ax & legacy for 2.4 / 5 GHz band
- Support 802.11ax only for 6GHz band
- Lead-free & Halogen-free design which is compliant with ROHS requirements.
- TX and RX low-density parity check (LDPC) support for improved range and power efficiency.
- Single-stream spatial multiplexing up to 600 Mbps data rate.
- 20, 40, 80 MHz bandwidth channels with optional SGI (1024 QAM modulation) for 5 / 6 GHz bands
- 20MHz channels for 2.4 GHz band with optional SGI (1024 QAM modulation)
- Supports standard SDIO v3.0/v2.0.

Bluetooth Key Feature

- BT host digital interface:
  - HCI UART (up to 4 Mbps)
  - PCM for audio data
- Complies with Bluetooth Core Specification Version 5.3 with provisions for supporting future specifications. With Bluetooth Class 1 or Class2 transmitter operation.
- Supports extended synchronous connections (eSCO), for enhanced voice quality by allowing for retransmission of dropped packets.
- Adaptive frequency hopping (AFH) for reducing radio frequency interference.
  A simplified block diagram of the module is depicted in the figure above.
- BT Core Specification Version 5.3, including the following support:
  - Low energy(LE) isochronous channels
  - LE power control
  - LE enhanced connection update
  - LE channel classification
  - LE audio

2. General Specification

2.1 General Specification

Model Name	AP6611S
Product Description	1T1R 802.11 a/b/g/n/ac/ax Wi-Fi 6E + BT 5.3 Module
Dimension	L x W : 12 x 12 (typical) mmp»H : 1.8 (Maximum) mm
Module type package	Stamp type with metal lid
Wi-Fi Interface	Support SDIO V3.0/ 2.0
BT Interface	UART / PCM
Operating temperature	-30°C to 85°C
Storage temperature	-40°C to 125°C
Humidity	Operating Humidity 10% to 95% Non-Condensing

Note:

The optimal RF performance specified in the data sheet, however, is guaranteed only -10 °C to +55 °C and 3.2V < VBAT < 3.8V without derating performance.

2.2 DC Characteristics

2.2.1 Absolute Maximum Ratings

Symbol	Description	Min.	Max.	Unit
VBAT	Input supply Voltage	3.0	4.8	V
VDDIO	Digital/Bluetooth/SDIO/ I/O Voltage	1.62	1.98	V

Note : RF performance is optimal for 3.2V ” 9 % $ 7 ” 9)MR’9 % $ 7 9 G H Y L F H U D G L will operate but RF performance will degrade.

2.2.2 Recommended Operating Rating

The module requires two power supplies: VBAT and VDDIO.

Voltage rails	Min.	Typ.	Max.	Unit
VBAT	3.2	3.3	4.8	V
VDDIO	1.62	1.8	1.98	V

VBAT current consumption 1000mA(Peak), when VBAT = 3.3V

The module requires two power supplies: other Digital I/O Pins.

For VDDIO=1.8V	Min.	Max.	Unit
Input high voltage	0.65 x VDDIO	NA	V
Input low voltage	NA	0.35 x VDDIO	V
Output high voltage @ 2mA	VDDIO t0.4	NA	V
Output low voltage @ 2mA	NA	0.4	V

3. Wi-Fi RF Specification

3.1 2.4GHz RF Specification

Conditions : VBAT=3.3V ; VDDIO=1.8V ; Temp=25°C

Feature	Description
WLAN Standard	IEEE 802.11 b/g/n/ax & Wi-Fi compliant
Frequency Range	2400 MHz ~ 2483.5 MHz (2.4GHz ISM Band)
Number of Channels	2400 MHz ~ 2483.5 MHzpÉCh1 ~ Ch13
Modulation	802.11b : DQPSK ã DBPSK ã CCK 802.11g/n : OFDM /64-QAM ã 16-QAM ã QPSK ã BPSK 802.11ax : OFDMA /256-QAM ã 64-QAM ã 16-QAM ã QPSK ã BPSK

Output Power , tolerance ± 1.5 dB The transmit EVM quality & spectrum mask are compliant with IEEE 802.11 standard					
802.11b	1Mbps	2Mbps	5.5Mbps	11Mbps	
	19	19	19	19	
802.11g	6 ã 9Mbps	12 ã 18Mbps	24Mbps	36Mbps	48Mbps
	19	19	18	18	17
	54Mbps				
	17				
802.11n 20MHz	MCS0~2	MCS3	MCS4	MCS5	MCS6
	18.5	18.5	18	17	16
	MCS7				
	16				
802.11ax 20MHz	HE0~2	HE3	HE4	HE5	HE6
	18.5	18.5	18	17	16
	HE7	HE8	HE9		
	16	15.5	15		

Note: The specifications of RF output power are subject to change to fulfill the safety regulation and requirements in end-user product.

Sensitivity, tolerance ± 2 dB CCK modulation PER ≦ 8%、OFDM modulation PER ≦ 10%				
802.11b	Data Rate	Spec.(dBm)		
	1Mbps	-96		
	2Mbps	-90		
	5.5Mbps	-88		
	11Mbps	-87		

802.11g	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	6Mbps	-91	**24Mbps**	-83
	9Mbps	-88	**36Mbps**	-80
	12Mbps	-87	**48Mbps**	-76
	18Mbps	-85	**54Mbps**	-73
802.11n_20MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-90	**MCS4**	-77
	MCS1	-87	**MCS5**	-75
	MCS2	-84	**MCS6**	-73
	MCS3	-80	**MCS7**	-72
802.11ax_20MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-90	**HE6**	-72
	HE1	-87	**HE7**	-71
	HE2	-84	**HE8**	-69
	HE3	-80	**HE9**	-68
	HE4	-77		
	HE5	-75		
Maximum Input Level	802.11b : -10 dBm			
	802.11g/n/ax : -20 dBm			

3.2 5 GHz RF Specification

Conditions : VBAT=3.3V ; VDDIO=1.8V ; Temp=25°C

Feature	Description
WLAN Standard	IEEE 802.11a/n/ac/ax & Wi-Fi compliant
Frequency Range	5150~5350MHz ã5470~5725MHz ã5725~5850MHz (5GHz UNII Band)
Number of Channels	5150~5350MHzpÉCh36 ~ Ch64 5470~5725MHzpÉCh100 ~ Ch140 5725~5850MHzpÉCh149 ~ Ch165
Modulation	802.11a : OFDM /64-QAM ã16-QAM ãQPSK ãBPSK 802.11n : OFDM /64-QAM ã16-QAM ãQPSK ãBPSK 802.11ac : OFDM /256-QAM ã64-QAM ã16-QAM ãQPSK ãBPSK 802.11ax : OFDMA /1024-QAM ã256-QAM ã64-QAM ã16-QAM ãQPSK ãBPSK

Output Power , tolerance ± 2 dB

The transmit EVM quality & spectrum mask are compliant with IEEE 802.11 standard

802.11a	**Frequency (MHz)**	**6~9Mbps**	**12~18Mbps**	**24Mbps**	**36Mbps**
	5150~5350	15.5	15.5	15.5	15.5
	5470~5725	15.5	15.5	15.5	15.5
	5725~5850	15.5	15.5	15.5	15.5
	Frequency (MHz)	**48Mbps**	**54Mbps**		
	5150~5350	15.5	15		
	5470~5725	15.5	15		
	5725~5850	15.5	15		
802.11n 20MHz	**Frequency (MHz)**	**MCS0~2**	**MCS3**	**MCS4**	**MCS5**
	5150~5350	15.5	15.5	15.5	15.5
	5470~5725	15.5	15.5	15.5	15.5
	5725~5850	15.5	1.5	15.5	15.5
	Frequency (MHz)	**MCS6**	**MCS7**		
	5150~5350	15	14		
	5470~5725	15	14		
	5725~5850	15	14		

802.11n 40MHz	**Frequency (MHz)**	**MCS0~2**	**MCS3**	**MCS4**	**MCS5**
	5150~5350	15	15	15	15
	5470~5725	15	15	15	15
	5725~5850	15	15	15	15
	Frequency (MHz)	**MCS6**	**MCS7**		
	5150~5350	15	14		
	5470~5725	15	14		
	5725~5850	15	14		
802.11ac 20MHz	**Frequency (MHz)**	**MCS0~2**	**MCS3**	**MCS4**	**MCS5**
	5150~5350	15.5	15.5	15.5	15.5
	5470~5725	15.5	15.5	15.5	15.5
	5725~5850	15.5	1.5	15.5	15.5
	Frequency (MHz)	**MCS6**	**MCS7**	**MCS8**	
	5150~5350	15	14.5	12.5	
	5470~5725	15	14.5	12.5	
	5725~5850	15	14.5	12.5	
802.11ac 40MHz	**Frequency (MHz)**	**MCS0~2**	**MCS3**	**MCS4**	**MCS5**
	5150~5350	15	15	15	15
	5470~5725	15	15	15	15
	5725~5850	15	15	15	15
	Frequency (MHz)	**MCS6**	**MCS7**	**MCS8**	**MCS9**
	5150~5350	15	14	12	11
	5470~5725	15	14	12	11
	5725~5850	15	14	12	11
802.11ac 80MHz	**Frequency (MHz)**	**MCS0~2**	**MCS3**	**MCS4**	**MCS5**
	5150~5350	15	15	15	15
	5470~5725	15	15	15	15
	5725~5850	15	15	15	15
	Frequency (MHz)	**MCS6**	**MCS7**	**MCS8**	**MCS9**
	5150~5350	15	13.5	12	11
	5470~5725	15	13.5	12	11
	5725~5850	15	13.5	12	11

	Frequency (MHz)	**HE0~2**	**HE3**	**HE4**	**HE5**
	5150~5350	15.5	15.5	15.5	15.5
	5470~5725	15.5	15.5	15.5	15.5
	5725~5850	15.5	1.5	15.5	15.5
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
802.11ax	**5150~5350**	15	14.5	12.5	12
20MHz	**5470~5725**	15	14.5	12.5	12
	5725~5850	15	14.5	12.5	12
	Frequency (MHz)	**HE10**	**HE11**		
	5150~5350	9.5	9.5		
	5470~5725	9.5	9.5		
	5725~5850	9.5	9.5		
	Frequency (MHz)	**HE0~2**	**HE3**	**HE4**	**HE5**
	5150~5350	15	15	15	15
	5470~5725	15	15	15	15
	5725~5850	15	15	15	15
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
802.11ax	**5150~5350**	15	14	12	11
40MHz	**5470~5725**	15	14	12	11
	5725~5850	15	14	12	11
	Frequency (MHz)	**HE10**	**HE11**		
	5150~5350	9	9		
	5470~5725	9	9		
	5725~5850	9	9		

802.11ax 80MHz	**Frequency (MHz)**	**HE0~2**	**HE3**	**HE4**	**HE5**
	5150~5350	15	15	15	15
	5470~5725	15	15	15	15
	5725~5850	15	15	15	15
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
	5150~5350	15	13.5	12	11
	5470~5725	15	13.5	12	11
	5725~5850	15	13.5	12	11
	Frequency (MHz)	**HE10**	**HE11**		
	5150~5350	8	8		
	5470~5725	8	8		
	5725~5850	8	8		
Note: The specifications of RF output power are subject to change to fulfill the safety regulation and requirements in end-user product.					

Sensitivity, tolerance ± 2 dB **CCK modulation PER ≦ 8%、OFDM modulation PER ≦ 10%**				
802.11a	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	6Mbps	-90	**24Mbps**	-83
	9Mbps	-90	**36Mbps**	-80
	12Mbps	-88	**48Mbps**	-75
	18Mbps	-86	**54Mbps**	-73
802.11n_20MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-90	**MCS4**	-79
	MCS1	-88	**MCS5**	-76
	MCS2	-86	**MCS6**	-73
	MCS3	-83	**MCS7**	-72
802.11n_40MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-88	**MCS4**	-77
	MCS1	-86	**MCS5**	-72
	MCS2	-83	**MCS6**	-70
	MCS3	-80	**MCS7**	-69
802.11ac_20MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-90	**MCS5**	-75
	MCS1	-88	**MCS6**	-73
	MCS2	-86	**MCS7**	-70
	MCS3	-83	**MCS8**	-68

	MCS4	-79		
802.11ac_40MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-88	**MCS5**	-72
	MCS1	-86	**MCS6**	-70
	MCS2	-83	**MCS7**	-69
	MCS3	-80	**MCS8**	-65
	MCS4	-76	**MCS9**	-64
802.11ac_80MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	MCS0	-85	**MCS5**	-68
	MCS1	-82	**MCS6**	-67
	MCS2	-79	**MCS7**	-65
	MCS3	-76	**MCS8**	-62
	MCS4	-73	**MCS9**	-61

802.11ax_20MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-90	**HE6**	-73
	HE1	-88	**HE7**	-70
	HE2	-86	**HE8**	-68
	HE3	-83	**HE9**	-64
	HE4	-79	**HE10**	-59
	HE5	-75	**HE11**	-57
802.11ax_40MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-88	**HE6**	-70
	HE1	-86	**HE7**	-69
	HE2	-83	**HE8**	-65
	HE3	-80	**HE9**	-64
	HE4	-76	**HE10**	-60
	HE5	-72	**HE11**	-55
802.11ax_80MHz	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-85	**HE6**	-67
	HE1	-82	**HE7**	-65
	HE2	-79	**HE8**	-62
	HE3	-76	**HE9**	-61
	HE4	-73	**HE10**	-57
	HE5	-68	**HE11**	-53
Maximum Input Level	802.11a/n/ac/ax : -30 dBm			

3.3 6GHz RF Specification

Conditions : VBAT=3.3V ; VDDIO=1.8V ; Temp=25°C

Feature	Description
WLAN Standard	IEEE 802.11ax & Wi-Fi compliant
Frequency Range	5925~7125MHz (6GHz U-NII5, U-NII6, U-NII-7, U-NII-8 Band)
Number of Channels	5925~6425MHzpÉ6G1 ~ 6G93 6425~6525MHzpÉ6G97 ~ 6G113 6525~6875MHzpÉ6G117~6G181 6875~7125MHzpÉ6G185~6G233
Modulation	802.11ax : OFDMA /1024-QAM ã256-QAM ã64-QAM ã16-QAM ãQPSK ãBPSK

Output Power , tolerance ± 2.5 dB

The transmit EVM quality & spectrum mask are compliant with IEEE 802.11 standard

802.11ax 20MHz	**Frequency (MHz)**	**HE0~2**	**HE3**	**HE4**	**HE5**
	5925~6425	14.5	14	14	14
	6425~6525	14.5	14	14	14
	6525~6875	14	14	14	14
	6875~7125	13.5	13.5	13.5	13.5
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
	5925~6425	14	13	11.5	10.5
	6425~6525	14	13	11.5	10.5
	6525~6875	14	13	11.5	10.5
	6875~7125	13	11	10.5	9.5
	Frequency (MHz)	**HE10**	**HE11**		
	5925~6425	9	9		
	6425~6525	9	9		
	6525~6875	9	9		
	6875~7125	8	8		
802.11ax 40MHz	**Frequency (MHz)**	**HE0~2**	**HE3**	**HE4**	**HE5**
	5925~6425	14.5	14	14	14
	6425~6525	14.5	14	14	14
	6525~6875	14	14	14	14
	6875~7125	14	13.5	13.5	13.5
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
	5925~6425	13.5	12.5	10.5	9
	6425~6525	13.5	12.5	10.5	9.5
	6525~6875	13.5	12.5	10.5	9.5

	6875~7125	13	11.5	9.5	8.5
	Frequency (MHz)	**HE10**	**HE11**		
	5925~6425	8	8		
	6425~6525	8.5	8.5		
	6525~6875	8.5	8.5		
	6875~7125	7.5	7.5		
802.11ax 80MHz	**Frequency (MHz)**	**HE0~2**	**HE3**	**HE4**	**HE5**
	5925~6425	14.5	14	14	14
	6425~6525	14.5	14	14	14
	6525~6875	14	14	14	14
	6875~7125	14	13.5	13.5	13.5
	Frequency (MHz)	**HE6**	**HE7**	**HE8**	**HE9**
	5925~6425	13.5	12.5	10.5	9.5
	6425~6525	13.5	12.5	10.5	9.5
	6525~6875	13.5	12.5	10.5	9.5
	6875~7125	13	11.5	9.5	8.5
	Frequency (MHz)	**HE10**	**HE11**		
	5925~6425	8.5	8.5		
	6425~6525	8.5	8.5		
	6525~6875	8.5	8.5		
	6875~7125	7.5	7.5		

Note: The specifications of RF output power are subject to change to fulfill the safety regulation and requirements in end-user product.

Sensitivity, tolerance ± 2 dB, OFDM modulation PER ¤ 10%

802.11ax_20MHz SISO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-88	**HE6**	-71
	HE1	-86	**HE7**	-68
	HE2	-84	**HE8**	-66
	HE3	-83	**HE9**	-62
	HE4	-77	**HE10**	-57
	HE5	-73	**HE11**	-55
802.11ax_20MHz MIMO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-88	**HE6**	-71
	HE1	-86	**HE7**	-68
	HE2	-84	**HE8**	-66
	HE3	-81	**HE9**	-62
	HE4	-77	**HE10**	-57

	HE5	-73	**HE11**	-54
802.11ax_40MHz SISO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-86	**HE6**	-68
	HE1	-84	**HE7**	-67
	HE2	-81	**HE8**	-63
	HE3	-78	**HE9**	-62
	HE4	-74	**HE10**	-68
	HE5	-70	**HE11**	-53
802.11ax_40MHz MIMO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-85	**HE6**	-68
	HE1	-84	**HE7**	-67
	HE2	-81	**HE8**	-63
	HE3	-78	**HE9**	-62
	HE4	-74	**HE10**	-58
	HE5	-70	**HE11**	-53
802.11ax_80MHz SISO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-83	**HE6**	-65
	HE1	-80	**HE7**	-63
	HE2	-77	**HE8**	-60
	HE3	-74	**HE9**	-59
	HE4	-71	**HE10**	-55
	HE5	-66	**HE11**	-51
802.11ax_80MHz MIMO	**Data Rate**	**Spec.(dBm)**	**Data Rate**	**Spec.(dBm)**
	HE0	-82	**HE6**	-65
	HE1	-80	**HE7**	-63
	HE2	-77	**HE8**	-60
	HE3	-74	**HE9**	-59
	HE4	-71	**HE10**	-55
	HE5	-66	**HE11**	-50
Maximum Input Level	802.11ax : -30dBm			

4. Bluetooth Specification

4.1 Bluetooth Specification

Conditions : VBAT=3.3V ; VDDIO=1.8V ; Temp=25°C

Feature	Description
General Specification	
Bluetooth Standard	BDR ã EDR(1Mbps & 2Mbps) ã LE(1Mbps) ã 2LE(2Mbps)
Host Interface	UART
Frequency Band	2402 MHz ~ 2480 MHz
Number of Channels	79 channels for classic 、40 channels for BLE
Modulation	' & ^ < U-DQPSK, 8DPSK
RF Specification	
Output Power , tolerance ± 2 dB	
	CL1 (dBm)
BDR Output Power	7
EDR Output Power	6
BLE Output Power	7
Sensitivity, tolerance ± 2 dB	
Sensitivity @ BER=0.1% for GFSK (1Mbps)	-87 dBm
Sensitivity @ BER=0.01% (} Œ -DQPSK (2Mbps)	-89 dBm
Sensitivity @ BER=0.01% for 8DPSK (3Mbps)	-84 dBm
Sensitivity @ PER=30.8% for LE (1Mbps)	-90 dBm
Sensitivity @ PER=30.8% for 2LE (2Mbps)	-90 dBm
Maximum Input Level	GFSK (1Mbps):-20dBm
	‹ lãDQPSK (2Mbps) :-20dBm
	8DPSK (3Mbps) :-20dBm

Note*：The Bluetooth BDR output power is able to be configured by firmware (hcd file).

5. Pin Definition

5.1 Pin Outline

PIN OUTLINE

<TOP VIEW>



5.2 Pin Assignment

NO	Name	Type	Description
1	GND	—	Ground connections
2	WL_BT_ANT	I/O	RF I/O port
3	GND	—	Ground connections
4	NC	p¼	& o } š] v P ~ } v [š } v v š š }
5	GND	—	Ground connections
6	BT_WAKE	I	HOST wake-up Bluetooth device
7	BT_HOST_WAKE	O	Bluetooth device to wake-up HOST
8	NC	p¼	& o } š] v P ~ } v [š } v v š š }
9	VBAT	P	Main power voltage source input
10	XTAL_IN	I	Crystal input
11	XTAL_OUT	O	Crystal output
12	WL_REG_ON	I	Power up/down internal regulators used by WiFi section
13	WL_HOST_WAKE	O	WLAN to wake-up HOST
14	SDIO_DATA_2	I/O	SDIO data line 2
15	SDIO_DATA_3	I/O	SDIO data line 3
16	SDIO_DATA_CMD	I/O	SDIO command line
17	SDIO_DATA_CLK	I/O	SDIO clock line
18	SDIO_DATA_0	I/O	SDIO data line 0
19	SDIO_DATA_1	I/O	SDIO data line 1
20	GND	—	Ground connections
21	ASR_VLX	O	Internal Analog Buck voltage generation pin
22	VDDIO	P	I/O Voltage supply input
23	ABUCK_1P12	I	Internal Analog Buck voltage generation pin
24	LPO	I	External Low Power Clock input (32.768KHz)
25	PCM_OUT	O	PCM Data output
26	PCM_CLK	I/O	PCM clock
27	PCM_IN	I	PCM data input
28	PCM_SYNC	I/O	PCM sync signal
29	NC	p¼	& o } š] v P ~ } v [š } v v š š }
30	NC	p¼	& o } š] v P ~ } v [š } v v š š }
31	GND	—	Ground connections
32	NC	p¼	& o } š] v P ~ } v [š } v v) š š }
33	GND	—	Ground connections
34	BT_REG_ON	I	Power up/down internal regulators used by BT section

35	WL_GPIO_2	I/O	This pin can be programmed to be a GPIO2
36	GND	—	Ground connections
37	WL_GPIO_1	I/O	This pin can be programmed to be a GPIO1 (WL_DEV_WAKE)
38	WL_GPIO_3	I/O	This pin can be programmed to be a GPIO3
39	WL_GPIO_4	I/O	This pin can be programmed to be a GPIO4
40	WL_GPIO_5	I/O	This pin can be programmed to be a GPIO5
41	UART_RTS_N	O	Bluetooth UART interface
42	UART_TXD	O	Bluetooth UART interface
43	UART_RXD	I	Bluetooth UART interface
44	UART_CTS_N	I	Bluetooth UART interface
45	WL_GPIO_5	I/O	This pin can be programmed to be a GPIO, or the GCI external coexistence interface.
46	NC	p¼	& o } š] v P ~ } v [š } v v š š }
47	NC	p¼	& o } š] v P ~ } v [š } v v š š }

6. Dimensions

6.1 Module Dimensions



6.2 Recommended footprint



- Solder paste layer design is generally the same as recommended footprint.
  (錫膏層設計通常建議和焊墊尺寸相同)
- If soldering quality with good wetting on upright side is essential for PQC, how to optimize the aperture design in the stencil to adjust the amount of solder paste would be crucial.
  In addition, a kind of stencil design with stepped thickness in partial area would be considered if the thickness of stencil is about 0.1mm or thinner. Please optimize the stencil design by manufacture engineer or contact AMPAK FAE for assistance.
  (如果模組吃錫品質考量側面爬錫，如何優化鋼網開孔設計以調整適當的錫膏量是非常重要的。尤其鋼網的厚度大約是 0.1mm 或更薄時，可考慮局部加厚鋼網的設計。請諮詢製程工程師以優化鋼網的設計,或是聯絡正基科技技術支持團隊).



External clock reference

External LPO signal characteristics

Parameter	Specification	Units
Nominal input frequency	32.768	kHz
Frequency accuracy	+/-25	ppm
Duty cycle	30 - 70	%
Input signal amplitude	1.8±0.09	V
Signal type	Square-wave or sine-wave	-
Input impedance	>100k <5	Ω pF
Clock jitter (integrated over 300Hz t 15KHz)	<1	Hz
Output high voltage	0.7Vio - Vio	V

External 37.4MHz Crystal characteristics

Parameter	Specification	Units
Nominal frequency - F0	37.4	MHz
Frequency Tolerance - 4 & l & ì (At 25oÎ +/- 3oÎ)	+/- 10	ppm
Operation Temperature Range - Topr	-30 ~ + 85	oÎ
Freq. Stability(over operating temperature) - TC Ref. to 25oÎ	+/- 10	ppm
Load capacitance - CL	18	pF
Equivalent Series Resistance t ESR	Max. 60	Ω
Drive Level - DL	Typ. 50, Max. 100	uW
Insulation resistance t IR At 100Vdc	Min. 500	MΩ

7. Host Interface Timing Diagram

8.1 Power-up Sequence Timing Diagram

The module has signals that allow the host to control power consumption by enabling or disabling the Bluetooth, WLAN and internal regulator blocks. These signals are described below.
Additionally, diagrams are provided to indicate proper sequencing of the signals for carious operating states. The timing value indicated are minimum required values: longer delays are also acceptable.

- z WL_REG_ON: Used by the PMU to power up or power down the internal regulators used by the WLAN section. When this pin is high, the regulators are enabled and the WLAN section is out of reset. When this pin is low the WLAN section is in reset.
- z BT_REG_ON: Used by the PMU to power up or power down the internal regulators used by the BT section. Low asserting reset for Bluetooth. This pin has no effect on WLAN and does not control any PMU functions. This pin must be driven high or low (not left floating).



*Notes:
1. The VBAT and VDDIO 10%–90% rise-time slopes must be greater than 50 microseconds/V.
2. VBAT should be up before or at the same time as VDDIO. VDDIO should NOT be present first or be held high before VBAT is high.

WLAN=ON, Bluetooth=ON



*Notes:
1. The VBAT and VDDIO 10%–90% rise-time slopes must be greater than 50 microseconds/V.
2. VBAT should be up before or at the same time as VDDIO. VDDIO should NOT be present first or be held high before VBAT is high.

WLAN=OFF, Bluetooth=OFF



***Notes:**
1. The VBAT and VDDIO 10%–90% rise-time slopes must be greater than 50 microseconds/V.
2. VBAT should be up before or at the same time as VDDIO. VDDIO should NOT be present first or be held high before VBAT is high.

WLAN=ON, Bluetooth=OFF



WLAN=OFF, Bluetooth=ON

8.2 SDIO Interface Description

The module supports SDIO version 3.0 for all 1.8V 4-bit UHSI speeds: SDR50(100 Mbps),SDR104(208MHz) and DDR50(50MHz, dual rates). It has the ability to stop the SDIO clock v u ‰ š Z]vš ŒŒµ‰š •]Pv o]vfš}v ['WJVŠK ŒŒ‰ŒEvµX‰ŠZ•]}PZ}µšv}š] when the WLAN device wants to turn on the SDIO interface. The ability to force the control of the gated clocks from within the WLAN chip is also provided.

- Function 0 Standard SDIO function (Max BlockSize / ByteCount = 32B)
- Function 1 Backplane Function to access the internal System On Chip (SOC) address space (Max BlockSize / ByteCount = 64B)
- Function 2 WLAN Function for efficient WLAN packet transfer through DMA (Max BlockSize/ByteCount=512B)

SDIO Pin Description

SD 4-Bit Mode	
DATA0	Data Line 0
DATA1	Data Line 1 or Interrupt
DATA2	Data Line 2 or Read Wait
DATA3	Data Line 3
CLK	Clock
CMD	Command Line

SDIO Default Mode Timing Diagram



Parameter	Symbol	Minimum	Typical	Maximum	Unit
SDIO CLK (All values are referred to minimum VIH and maximum VIL[b])					
Frequency – Data Transfer mode	fPP	0	–	25	MHz
Frequency – Identification mode	fOD	0	–	400	kHz
Clock low time	tWL	10	–	–	ns
Clock high time	tWH	10	–	–	ns
Clock rise time	tTLH	–	–	10	ns
Clock low time	tTHL	–	–	10	ns
Inputs: CMD, DAT (referenced to CLK)					
Input setup time	tISU	5	–	–	ns
Input hold time	tIH	5	–	–	ns
Outputs: CMD, DAT (referenced to CLK)					
Output delay time – Data Transfer mode	tODLY	0	–	14	ns
Output delay time – Identification mode	tODLY	0	–	50	ns

a. Timing is based on CL ≤ 40pF load on CMD and Data.
b. min(Vih) = 0.7 × VDDIO and max(Vil) = 0.2 × VDDIO.

SDIO High Speed Mode Timing Diagram



Parameter	*Symbol*	*Minimum*	*Typical*	*Maximum*	*Unit*
SDIO CLK (all values are referred to minimum VIH and maximum VIL[b])					
Frequency – Data Transfer Mode	fPP	0	–	50	MHz
Frequency – Identification Mode	fOD	0	–	400	kHz
Clock low time	tWL	7	–	–	ns
Clock high time	tWH	7	–	–	ns
Clock rise time	tTLH	–	–	3	ns
Clock low time	tTHL	–	–	3	ns
Inputs: CMD, DAT (referenced to CLK)					
Input setup Time	tISU	6	–	–	ns
Input hold Time	tIH	2	–	–	ns
Outputs: CMD, DAT (referenced to CLK)					
Output delay time – Data Transfer Mode	tODLY	–	–	14	ns
Output hold time	tOH	2.5	–	–	ns
Total system capacitance (each line)	CL	–	–	40	pF

a. Timing is based on CL ≤ 40 pF load on CMD and Data.
b. min(Vih) = 0.7 × VDDIO and max(Vil) = 0.2 × VDDIO.

SDIO Bus Timing Specifications in SDR Modes

Clock timing (SDR Modes)



Parameter	Symbol	Minimum	Maximum	Unit	Comments
–	t_{CLK}	40	–	ns	SDR12 mode
		20	–	ns	SDR25 mode
		10	–	ns	SDR50 mode
		4.8	–	ns	SDR104 mode
–	t_{CR}, t_{CF}	–	0.2 × t_{CLK}	ns	t_{CR}, t_{CF} < 2.00 ns (max) @100 MHz, C_{CARD} = 10 pF t_{CR}, t_{CF} < 0.96 ns (max) @208 MHz, C_{CARD} = 10 pF
Clock duty	–	30	70	%	–

SDIO Bus Input timing (SDR Modes)



Symbol	Minimum	Maximum	Unit	Comments
SDR104 Mode				
t_{IS}	1.4	–	ns	C_{CARD} = 10 pF, VCT = 0.975V
t_{IH}	0.80	–	ns	C_{CARD} = 5 pF, VCT = 0.975V
SDR50 Mode				
t_{IS}	3.00	–	ns	C_{CARD} = 10 pF, VCT = 0.975V
t_{IH}	0.80	–	ns	C_{CARD} = 5 pF, VCT = 0.975V

SDIO Bus output timing (SDR Modes up to 100MHz)



Symbol	Minimum	Maximum	Unit	Comments
t_{ODLY}	–	7.5	ns	$t_{CLK} \geq 10$ ns $C_L = 30$ pF using driver type B for SDR50
t_{ODLY}	–	14.0	ns	$t_{CLK} \geq 20$ ns $C_L = 40$ pF using for SDR12, SDR25
t_{OH}	1.5	–	ns	Hold time at the t_{ODLY} (min) $C_L = 15$ pF

Card output timing (SDR Modes 100MHz to 208MHz)



Symbol	Minimum	Maximum	Unit	Comments
t_{OP}	0	2	UI	Card output phase
Δt_{OP}	–350	+1550	ps	Delay variation due to temp change after tuning
t_{ODW}	0.60	–	UI	t_{ODW}=2.88 ns @208 MHz

- Δt_{OP} = +1550 ps for junction temperature of Δt_{OP} = 90 degrees during operation
- Δt_{OP} = –350 ps for junction temperature of Δt_{OP} = –20 degrees during operation
- Δt_{OP} = +2600 ps for junction temperature of Δt_{OP} = –20 to +125 degrees during operation

Δt_{OP} Consideration for Variable Data Window (SDR 104 Mode)



SDIO Bus Timing Specifications in DDR50 Mode



Parameter	Symbol	Minimum	Maximum	Unit	Comments
–	t_{CLK}	20	–	ns	DDR50 mode
–	t_{CR},t_{CF}	–	0.2 × tCLK	ns	t_{CR}, t_{CF} < 4.00 ns (max) @50 MHz, C_{CARD} = 10 pF
Clock duty	–	45	55	%	–

Data Timing



Parameter	Symbol	Minimum	Maximum	Unit	Comments
Input CMD					
Input setup time	t_{ISU}	6	–	ns	C_{CARD} < 10 pF (1 Card)
Input hold time	t_{IH}	0.8	–	ns	C_{CARD} < 10 pF (1 Card)
Output CMD					
Output delay time	t_{ODLY}	–	13.7	ns	C_{CARD} < 30 pF (1 Card)
Output hold time	t_{OH}	1.5	–	ns	C_{CARD} < 15 pF (1 Card)
Input DAT					
Input setup time	t_{ISU2x}	3	–	ns	C_{CARD} < 10 pF (1 Card)
Input hold time	t_{IH2x}	0.8	–	ns	C_{CARD} < 10 pF (1 Card)
Output DAT					
Output delay time	t_{ODLY2x}	–	7.5	ns	C_{CARD} < 25 pF (1 Card)
Output hold time	t_{ODLY2x}	1.5	–	ns	C_{CARD} < 15 pF (1 Card)

8.3 PCM Interface Description

The PCM Interface on the AP6611S can connect to linear PCM Codec devices in master or slave mode. In master mode, the AP6611S generates the PCM_CLK and PCM_SYNC signals, and in slave mode, these signals are provided by another master on the PCM interface and are inputs to the AP6611S.The configuration of the PCM interface may be adjusted by the host through the use of vendor-specific HCI commands.

Short Frame Sync, Master Modem

PCM Timing Diagram (Short Frame Sync, Master Mode)



PCM Interface Timing Specifications (Short Frame Sync, Master Mode)

Reference	Characteristics	Minimum	Typical	Maximum	Unit
1	PCM bit clock frequency		–	12	MHz
2	PCM bit clock low	41	–	–	ns
3	PCM bit clock high	41	–	–	ns
4	PCM_SYNC delay	0	–	25	ns
5	PCM_OUT delay	0	–	25	ns
6	PCM_IN setup	8	–	–	ns
7	PCM_IN hold	8	–	–	ns
8	Delay from rising edge of PCM_BCLK during last bit period to PCM_OUT becoming high impedance	0	–	25	ns

Short Frame Sync, Slave Mode

PCM Timing Diagram (Short Frame Sync, Slave Mode)



PCM Interface Timing Specifications (Short Frame Sync, Slave Mode)

Reference	Characteristics	Minimum	Typical	Maximum	Unit
1	PCM bit clock frequency	–	–	12	MHz
2	PCM bit clock low	41	–	–	ns
3	PCM bit clock high	41	–	–	ns
4	PCM_SYNC setup	8	–	–	ns
5	PCM_SYNC hold	8	–	–	ns
6	PCM_OUT delay	0	–	25	ns
7	PCM_IN setup	8	–	–	ns
8	PCM_IN hold	8	–	–	ns
9	Delay from rising edge of PCM_BCLK during last bit period to PCM_OUT becoming high impedance	0	–	25	ns

Long Frame Sync, Master Mode

PCM Timing Diagram (Long Frame Sync, Master Mode)



PCM Interface Timing Specifications (Long Frame Sync, Master Mode)

Reference	*Characteristics*	*Minimum*	*Typical*	*Maximum*	*Unit*
1	PCM bit clock frequency	–	–	12	MHz
2	PCM bit clock low	41	–	–	ns
3	PCM bit clock high	41	–	–	ns
4	PCM_SYNC delay	0	–	25	ns
5	PCM_OUT delay	0	–	25	ns
6	PCM_IN setup	8	–	–	ns
7	PCM_IN hold	8	–	–	ns
8	Delay from rising edge of PCM_BCLK during last bit period to PCM_OUT becoming high impedance	0	–	25	ns

Long Frame Sync, Slave Mode

PCM Timing Diagram (Long Frame Sync, Slave Mode)



PCM Interface Timing Specifications (Long Frame Sync, Slave Mode)

Reference	*Characteristics*	*Minimum*	*Typical*	*Maximum*	*Unit*
1	PCM bit clock frequency	–	–	12	MHz
2	PCM bit clock low	41	–	–	ns
3	PCM bit clock high	41	–	–	ns
4	PCM_SYNC setup	8	–	–	ns
5	PCM_SYNC hold	8	–	–	ns
6	PCM_OUT delay	0	–	25	ns
7	PCM_IN setup	8	–	–	ns
8	PCM_IN hold	8	–	–	ns
9	Delay from rising edge of PCM_BCLK during last bit period to PCM_OUT becoming high impedance	0	–	25	ns

Short Frame Sync, Burst Mode

PCM Burst Mode Timing (Receive Only, Short Frame Sync)



PCM Burst Mode (Receive Only, Short Frame Sync)

Reference	Characteristics	Minimum	Typical	Maximum	Unit
1	PCM bit clock frequency	–	–	24	MHz
2	PCM bit clock low	20.8	–	–	ns
3	PCM bit clock high	20.8	–	–	ns
4	PCM_SYNC setup	8	–	–	ns
5	PCM_SYNC hold	8	–	–	ns
6	PCM_IN setup	8	–	–	ns
7	PCM_IN hold	8	–	–	ns

Long Frame Sync, Burst Mode

PCM Burst Mode Timing (Receive Only, Long Frame Sync)



PCM Burst Mode (Receive Only, Long Frame Sync)

Reference	Characteristics	Minimum	Typical	Maximum	Unit
1	PCM bit clock frequency			24	MHz